

**DIECI**



# CONSTRUCTION RANGE

DIECI CONSTRUCTION RANGE OF TELEHANDLERS & TRUCK MIXERS

# STANDARD



MODEL	APOLLO 25.6	DEDALUS 30.7 TCL	DEDALUS 30.7 TCH	DEDALUS 30.9 TCL	DEDALUS 30.9 TCH
Engine	Kubota	Kubota	Kubota	Kubota	Kubota
Maximum power	55.4 kW (74 HP)	73.4 kW (98HP)	73.4 kW (98HP)	73.4 kW (98HP)	73.4 kW (98HP)
Emission Standard	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3
Maximum speed	30 km/h (18.6 mph)	35 km/h (21.7 mph)	35 km/h (21.7 mph)	35 km/h (21.7 mph)	35 km/h (21.7 mph)
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Maximum capacity	2500 kg (5512 lb)	3000 kg (6614 lb)	3000 kg (6614 lb)	3000 kg (6614 lb)	3000 kg (6614 lb)
Maximum lift height	5.78 m (19 ft)	6.35 m (20.8 ft)	6.45 m (21.1 ft)	8.60 m (28.2 ft)	8.70 m (28.5 ft)
Length	4125 mm (162.4 in)	4765 mm (187.6 in)	4765 mm (187.6 in)	4775 mm (188 in)	4775 mm (188 in)
Width	1850 mm (72.8 in)	2000 mm (78.7 in)	2000 mm (78.7 in)	2000 mm (78.7 in)	2000 mm (78.7 in)
Height	1950 mm (72.8 in)	2040 mm (80.3 in)	2220 mm (87.4 in)	2040 mm (80.3 in)	2220 mm (87.4 in)
Unladen weight	5100 kg (11244 lb)	6100 kg (13448 lb)	6100 kg (13448 lb)	6250 kg (13779 lb)	6250 kg (13779 lb)
Tyres	12x16.5"	12.5x18"	400/70x20"	12.5x18"	400/70x20"



ZEUS 33.11	ZEUS 35.10	ZEUS 40.7	RUNNER 40.13	ICARUS 40.17	SAMSON 70.10
FPT	FPT	FPT	FPT	FPT	FPT
93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)
Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3
40 km/h (24.9 mph)	30 km/h (21.7 mph)	40 km/h (24.9 mph)	40 km/h (24.9 mph)	35 km/h (21.7 mph)	30 km/h (18.6 mph)
Hydrostatic	Hydrostatic	Power Shift	Hydrostatic	Hydrostatic	Hydrostatic
3300 kg (7275 lb)	3800 kg (8378 lb)	4000 kg (8818 lb)	4000 kg (8818 lb)	4000 kg (8818 lb)	7000 kg (15432 lb)
10.60 m (34.8 ft)	9.75 m (32 ft)	7.00 m (23 ft)	12.20 m (40 ft)	16.70 m (54.8 ft)	9.50 m (31.2 ft)
5300 mm (208.7 in)	4950 mm (194.9 in)	5075 mm (199.8 in)	5590 mm (220.1 in)	6275 mm (247 in)	5910 mm (323.7 in)
2290 mm (90.2 in)	2290 mm (90.2 in)	2260 mm (71.7 in)	2480 mm (97.6 in)	3270 mm (128.7 in)	2380 mm (93.7 in)
2310 mm (90.9 in)	2310 mm (90.9 in)	2445 mm (96.3 in)	2460 mm (96.9 in)	2550 mm (100.4 in)	2490 mm (232.7 in)
8200 kg (18078 lb)	8000 kg (13448 lb)	7700 kg (16976 lb)	10420 kg (22972 lb)	12260 kg (27029 lb)	12100 kg (26676 lb)
400/70x20"	400/70x20"	400/70x24"	18x22.5"	18x22.5"	445/65R22.5"

# HEAVY



MODEL	HERCULES 100.10	HERCULES 120.10	HERCULES 190.10	HERCULES 210 .10
Engine	FPT	Kubota	FPT	FPT
Maximum power	104 kW (139 HP)	73.4 kW (98HP)	93 kW (125 HP)	93 kW (125 HP)
Emission Standard	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3
Maximum speed	35 km/h (21.7 mph)	35 km/h (21.7 mph)	40 km/h (24.9 mph)	35 km/h (21.7 mph)
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Maximum capacity	10000 kg (22046 lb)	12000 kg (26455 lb)	19000 kg (41888 lb)	21000 kg (60627 lb)
Maximum lift height	9.50 m (31.2 ft)	9.50 m (31.2 ft)	10.20 m (33.5 ft)	10.20 m (33.5 ft)
Length	6050 mm (238.2 in)	6050 mm (238.2 in)	6800 mm (267.7 in)	6800 mm (267.7 in)
Width	2420 mm (95.3 in)	2420 mm (95.3 in)	2600 mm (102.4 in)	2700 mm (106.3 in)
Height	2890 mm (113.8 in)	2890 mm (113.8 in)	2930 mm (115.4 in)	2930 mm (115.4 in)
Unladen weight	16000 kg (35274 lb)	16800 kg (37038 lb)	24500 kg (54013 lb)	27500 kg (60627 lb)
Tyres	17.5x25"	17.5x25"	20.5R25"	23.5R25"

# ROTATING



MODEL	PEGASUS 38.16 400°	PEGASUS 40.18 400°
Engine	Kubota	Kubota
Maximum power	73.4 kW (98HP)	73.4 kW (98HP)
Emission Standard	Stage IIIA/Tier 3	Stage IIIA/Tier 3
Maximum speed	25 km/h (15.5 mph)	25 km/h (15.5 mph)
Transmission	Hydrostatic	Hydrostatic
Maximum capacity	3800 kg (8378 lb)	4000 kg (8818 lb)
Maximum lift height	15.70 m (51.5 ft)	18 m (59.1 ft)
Length	6740 mm (265.4 in)	6630 mm (261 in)
Width	2380 mm (93.7 in)	2380 mm (93.7 in)
Height	3035 mm (119.5 in)	3035 mm (119.5 in)
Unladen weight	13200 kg (29101 lb)	13700 kg (30203 lb)
Tyres	400/70R20"	400/70R20"




MODEL	PEGASUS 50.19 360°	PEGASUS 50.21 360°	PEGASUS 60.16 360°
Engine	FPT	FPT	FPT
Maximum power	104 kW (139 HP)	104 kW (139 HP)	104 kW (139 HP)
Emission Standard	Stage IIIA/Tier 3	Stage IIIA/Tier 3	Stage IIIA/Tier 3
Maximum speed	40 km/h (24.9 mph)	40 km/h (24.9 mph)	40 km/h (24.9 mph)
Transmission	Hydrostatic	Hydrostatic	Hydrostatic
Maximum capacity	5000 kg (11023 lb)	5000 kg (11023 lb)	6000 kg (13228 lb)
Maximum lift height	18.70 m (61.4 ft)	20.50 m (67.3 ft)	15.70 m (51.5 ft)
Length	6800 mm (267.7 in)	7150 mm (281.5 in)	6720 mm (264.6 in)
Width	2380 mm (93.7 in)	2380 mm (93.7 in)	2380 mm (93.7 in)
Height	3020 mm (118.9 in)	3020 mm (118.9 in)	3020 mm (118.9 in)
Unladen weight	16500 kg (36376 lb)	17540 kg (38669 lb)	16600 kg (36597 lb)
Tyres	445/65R22.5" (18R22.5")	445/65R22.5" (18R22.5")	445/65R22.5" (18R22.5")





Distributed by Dieci Australia and their network of authorised dealers.

Unit 1/5 Melito Court, Prestons NSW 2170  
[www.dieciaustralia.com.au](http://www.dieciaustralia.com.au) | [info@dieciaustralia.com.au](mailto:info@dieciaustralia.com.au)  
Tel. +61 2 8795 4555



Illustrations and photos show the standard international models and may or may not include optional equipment, accessories, customer installed or modified parts, optional parts and all standard equipment with some differences in colour and features. Machine specifications are subject to change without notice and additional load charts and machine or attachment specifications may be available on request. Please refer to the operators manual for correct machine and attachment operation.

Printed in Australia SKT Construction Range EXTRA-EC-AU | 2.1\_2020